

Product datasheet

USB-Switch++ M



- USB-controlled two relays mains switch equipped with german Schuko mains plug and socket
- Phase and neutral conductor are connected and disconnected simultaneously
- Switches 230V / 16 A, max 3,500 W (single phase motor rating max. 550 W) using two extrem reliable Finder®-Relais
- **Automatic power-off** if no security code is received
Monitoring period adjustable 1-100 seconds
- Multiple USB-Switches at a single PC controlled by the serial number
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching in scripts and batches
- No driver installation needed with Windows® x86/x64 variants.
(® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- [API](#) - Application Program Interface for easy integration in user applications
- [Linux](#) support available.
- Use with LabView® possible
- RoHS, CE & EN60950 conform / IP20
- About 120 mA power consumption when turned on
- Dimension about 96 x 63 x 87 mm
- USB cable length about 2 m
- For indoor use only
- 2-year warranty
- Made in Germany
- Product link : www.cleware-shop.de/USB-Switch-EN
- **Customs Tarif number: 85369095**
- **Country of origin: Deutschland**

Artikel	Article-Nr.	USB cable length (Meter)	Weight (Gramm)	Length (mm)	Width (mm)	Height (mm)
USB-Switch++M	40-1	2 m	240	96	63	87